

# UNIVERSAL INTERIOR PRIMER

primer

---

<b>PAINT TYPE</b>	Water-borne, full-matt dispersion paint containing acrylate for interior painting.
<b>USAGE</b>	<p>The paint is suitable for new and previously painted surfaces of concrete, plaster, filler, brick and building boards. As a primer the paint is well overcoatable with dispersion paints of different gloss.</p> <p>The product has been classified in Emission Classification of building materials to <b>Group M1</b>.</p>

---

**TECHNICAL DATA**

<b>Solids</b>	About 31 % by volume						
<b>Volatile organic compound (VOC)</b>	EU VOC limit value (kat A/g): 30 g/l. The product's VOC: max. 30 g/l.						
<b>Practical spreading rate</b>	<table><tr><td>Previously painted surface</td><td>7 - 10 m<sup>2</sup>/l</td></tr><tr><td>Filler and wood fibre board</td><td>5 - 8 m<sup>2</sup>/l</td></tr><tr><td>Concrete and plastered surface</td><td>4 - 7 m<sup>2</sup>/l</td></tr></table>	Previously painted surface	7 - 10 m <sup>2</sup> /l	Filler and wood fibre board	5 - 8 m <sup>2</sup> /l	Concrete and plastered surface	4 - 7 m <sup>2</sup> /l
Previously painted surface	7 - 10 m <sup>2</sup> /l						
Filler and wood fibre board	5 - 8 m <sup>2</sup> /l						
Concrete and plastered surface	4 - 7 m <sup>2</sup> /l						
<b>Density</b>	abt. 1.4 g/ml						
<b>Drying time at +23°C / 50% RH</b>							
- dust free	after ½ hour						
- overcoatable	after 1 hour						
	The drying will be slowed down if the air is cool and/or humid.						
<b>Thinner, clean up</b>	Water. Wash the equipment immediately after use with water.						
<b>Finish</b>	Full-matt						
<b>Colours</b>	White. Can be tinted with tinting pastes to light shades according to the Interior Colour Cards. The colour accuracy is not complete.						
<b>Washability and wear resistance</b>	Wet scrub resistance, class 3 according to EN 13300 (ISO 11998).						
<b>Packages</b> (availability varies by country)	<b>White:</b> 2,7 L, 9 L						

---

<b>SAFETY MARKINGS</b>	See Safety Data Sheet.
------------------------	------------------------

---

**DIRECTION FOR USE****Surface preparation**

Clean new surfaces from dust and dirt.  
Wash previously painted surfaces with paint cleaner.  
Matt down hard or gloss surfaces by sanding and thereafter remove the dust.  
Remove all of the old paint from the surfaces which have been painted with glue paint or lime wash.  
Smooth any irregularities in the surface with a suitable filler. The dried filler is sanded down and the dust removed.

**Application**

Before use stir the paint thoroughly.  
Apply once or twice by brush, roller or spray.

**Application conditions**

The surface to be painted has to be dry. During the application and drying period the temperature of the ambient air, the surface and the paint shall be above +5°C and the relative air humidity below 80%.

Good ventilation during the application and drying period quickens the drying process.

**Storage**

Must not freeze.

---

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages [www.teknos.com](http://www.teknos.com).

---



EN\_2369\_Tuoteseloste.pdf